

MATERIAL SAFETY DATA SHEET

A.P. GREEN INDUSTRIES, INC.
GREEN BOULEVARD, MEXICO, MO 65265
TELEPHONE NUMBER - 573-473-3626

SECTION I**PRODUCT NAME:** A.P. GREEN INSULATING CEMENT-P**FORMULA:** NOT APPLICABLE**PRODUCT TYPE:** HIGH TEMPERATURE INSULATING CEMENT**NFPA RATING:** 1-0-0-0**CHEMICAL FAMILY:** NOT APPLICABLE**DOT NO:** NOT REGULATED**SECTION II****PRODUCT HAZARDOUS INGREDIENTS**

<u>MATERIAL</u>	<u>TLV-TWA</u>	<u>CAS #</u>	<u>PERCENT</u>
Mineral Wool Fiber	10 mg/M ³ total 5 mg/M ³ respirable	None Assigned	25-35
Bentonite Colloidal Clay	10 mg/M ³ total 5 mg/M ³ respirable	1302-78-9	35-45
Calcium Carbonate	10 mg/M ³ total 5 mg/M ³ respirable	1317-65-3	20-30
Rust Inhibitor (Compounds of Sodium)	10 mg/M ³ total 5 mg/M ³ respirable	7632-00-0	<1

* A.P. Green work place exposure guideline. See also Section III

Note: International Agency for Research on Cancer (IARC) has classified crystalline silica in the category of Group 1 and continues to classify mineral wool fiber in the category of 2B.

SECTION III**HAZARDS INFORMATION**

This product contains crystalline silica. Prolonged exposure to dust may cause silicosis, a progressive pneumoconiosis, or other respiratory diseases. International Agency for Research on Cancer (IARC) has classified crystalline silica as Group 1. The agency states there is sufficient evidence of carcinogenicity in humans. Reference: IARC Monograph 68.

Dust from product at any stage of its use or during tear-out after service may, especially on long term exposure, lead to lung disease unless respiratory protection is employed. NIOSH approved respirators should be worn any time that refractories are torn out after service. While a respiratory hazard and/or nuisance dust may exist from the product itself, other foreign substances may warrant additional precautions during tear-out and disposal.

SECTION IV**FIRE AND EXPLOSION HAZARD DATA****FLASH POINT:** Non-Combustible**EXTINGUISHING MEDIA:** Material compatible with CO₂, water or dry chemical extinguishing media.**SPECIAL FIRE FIGHTING PROCEDURES:** None**UNUSUAL FIRE AND EXPLOSION HAZARDS:** None

SECTION V
FIRST AID AND HEALTH HAZARD DATA

EFFECT OF OVEREXPOSURE:

EYES: ACUTE: May causes irritation.
CHRONIC: None known.
SKIN: ACUTE: May cause skin irritation.
CHRONIC: None known.
INHALATION: ACUTE: May cause upper respiratory irritation.
CHRONIC: Prolonged irritation of mineral wool dust may reduce lung function.

EFFECTS OF OVEREXPOSURE:

INGESTION: ACUTE: CONSULT A PHYSICIAN IMMEDIATELY.

EMERGENCY AND FIRST AID PROCEDURES:

EYES: Immediately rinse eyes with plenty of water until irritation stops.
SKIN: Wash frequently with soap and water to minimize irritation.
INHALATION: Remove to fresh air. Remove fibers and dust from nose and drink water to clear throat.
INGESTION: Consult a physician immediately.

NOTE: Should any of the above conditions persist, consult a physician.

SECTION VI
ACCIDENTAL RELEASE MEASURES

SPILLS: Avoid creating dust, use a vacuum or wet clean-up to minimize dust.

WASTE DISPOSAL: Mineral wool fiber products are generally classified as a non-hazardous waste and may be disposed of in a non-critical landfill. Always check all local, state and federal regulations.

SECTION VII
HANDLING AND STORAGE

Store in dry area. Product is non-flammable.

SECTION VIII
EXPOSURE CONTROLS AND PERSONAL PROTECTION

RESPIRATORY PROTECTION: Wear NIOSH/MSHA approved respirators.

VENTILATION: Use sufficient ventilation (natural or mechanical) while handling this material in a dry state, to maintain airborne dust levels below TLV.

EYE PROTECTION: Safety glasses or goggles should be worn when materials are being handled.

GENERAL INFORMATION: Use waterproof or rubber gloves to protect hands. Clothing should be long sleeved, loose fitting and a cap should be worn. Wash all work clothing separate from other clothing to prevent possible migration of mineral wool fiber and dust to other clothes.

SECTION IX
CHEMICAL AND PHYSICAL PROPERTIES

APPEARANCE AND ODOR: DRY, GRANULAR MIXTURE, GRAY IN COLOR.

BOILING POINT: N/A

MELTING POINT: N/A

SOLUBILITY IN WATER: N/A

pH: 9.5 to 10.5

ODOR: NONE

SECTION X
STABILITY AND REACTIVITY

This product is stable under normal conditions of use, storage and transportation.

This product can react with strong acids.

SECTION XI
TOXICOLOGICAL INFORMATION

LD₅₀ or LC₅₀ for oral, dermal, or inhalation routes of administration: No data for product.

SECTION XII
ECOLOGICAL INFORMATION

Ecotoxicological/chemical fate information: Not available.

SECTION XIII
DISPOSAL CONSIDERATIONS

As supplied, product may be disposed of in an approved landfill, in accordance with federal, state and local regulations.

Supplier can make no statement concerning disposal of used product, since product may become contaminated by hazardous materials during use.

SECTION XIV
TRANSPORTATION INFORMATION

U.S.A. DOT: Not regulated.
Canadian TDG Hazard Class & PIN: Not regulated.

SECTION XV
REGULATORY INFORMATION

TSCA Status: All components listed.

Canadian DSL: All components listed.

SARA Title III, Section 313: This MSDS provides the toxic chemical "SUPPLIER INFORMATION" required under Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and 40 CFR 372. Toxic chemical information, if applicable to the product(s) named, is located in Section II - HAZARDOUS INGREDIENTS section of the MSDS.

SECTION XVI
OTHER INFORMATION

MSDS Status: Replaces MSDS Dated 11/02/94

Note: This material safety data sheet contains confidential proprietary information and is not to be disclosed to the general public or to competition except as required by law. The information accumulated herein is believed to be accurate but is not warranted to be, whether originating with A.P. Green Industries, Inc. or not. This information is offered solely for use in your evaluation of this product in respect to safety, health, and environmental hazards.

MANUFACTURED BY: P.K. INSULATION MFG. CO., INC. JOPLIN, MO
CURRENT MSDS DATE 09/29/97