



MATERIAL SAFETY DATA SHEET

REVISION DATE: 10/28/2008
DATE PRINTED: 11/11/2008

REVISION NUMBER: 2
PREPARED BY: Walter Friedlander

1. CHEMICAL PRODUCT

PRODUCT NAME: **INTEC MULTI-SOL #3366, New and Improved**
PRODUCT CODE: 118155

NFPA/HMIS HAZARD CODES(minimal=0; slight=1; moderate=2; serious=3; severe=4)

Health: 1/1 Fire: 1/1
Reactivity: 0/0 Special/Protective Equipment: None/B

NAME OF THE MANUFACTURER: Rochester Midland Corporation
333 Hollenbeck Street
Rochester, New York 14621
Information: 585-336-2200
Emergency Phone:
INFOTRAC: 1-800-535-5053
OUTSIDE US: 1-352-323-3500

2. HAZARDS IDENTIFICATION

EFFECTS FROM ACUTE EXPOSURE:

INGESTION: Irritation of the mouth, throat, and stomach. May act as a laxative or cause other internal effects. Aspiration of ingested or vomited liquid into the lungs may cause chemical pneumonia, which can be fatal.

SKIN CONTACT: Prolonged contact may lead to irritation and dermatitis.

INHALATION: Coughing, chest pains, and breathing difficulty may occur.

EYE CONTACT: Causes moderate eye irritation.

CHRONIC EFFECTS: Dermatitis. Prolonged or repeated inhalation of high concentration of mist may cause a benign form of pulmonary fibrosis.

EFFECTS/CARCINOGENICITY: MIST 5 mg/m³ TLV (8-hour time-weighted average exposure: OSHA 29 CFR 1910.1000, Table Z-1). Avoid unnecessary exposure to liquid oil.

ROUTES OF ENTRY: Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation.

3. COMPOSITION/INFORMATION ON INGREDIENTS

PRODUCT COMPOSITION CAS#	%	ACGIH TLV	OSHA PELs
Naphthenic oil 64742-53-6	75 - 80	NA	NA

4. FIRST AID MEASURES

INGESTION: DO NOT INDUCE VOMITING. Get immediate medical attention. May cause aspiration pneumonia.

SKIN: Wash with soap and water. Remove contaminated clothing and launder before reuse.

INHALATION: If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.

EYES: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

NOTES TO PHYSICIAN: None.

5. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (F): > 320 F (ASTM D-56) (C): NA

INTEC MULTI-SOL #3366, New and Improved

5. FIRE AND EXPLOSION HAZARD DATA

METHOD: ASTM D-56

FLAMMABLE LIMITS IN AIR

- LOWER (%): NE
- UPPER (%): NE

SENSITIVITY TO MECHANICAL IMPACT(Y/N):

NO

SENSITIVITY TO STATIC DISCHARGE:

Sensitivity to static discharge is not expected.

SUITABLE EXTINGUISHING MEDIA:

Carbon Dioxide, Dry Chemicals, Foam. Sand.

FIRE FIGHTING PROCEDURES:

Fire-fighters should wear self-contained breathing apparatus and full protective clothing when fighting chemical fires. Cool exposed containers with water spray. DO NOT USE streams of water, as this will scatter the liquid and spread the fire. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

6. ACCIDENTAL RELEASE MEASURES

SPILL PROCEDURES:

SMALL SPILLS:

Reclaim as much as possible.

LARGE SPILLS:

Dike to contain. Pick up with absorbant material. Put in suitable container for disposal. Keep out of drains, sewers, streams, or other bodies of water.

PERSONAL PRECAUTIONS:

NA

ENVIRONMENTAL PRECAUTIONS:

NA

METHODS FOR CLEANING UP:

NA

7. HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN
IN HANDLING AND STORAGE:

Store in a cool, dry area. Do not expose to extreme temperatures. Store in a well ventilated area. Do not store near oxidizing agents. Do not breathe mist or vapors. Bond and ground during liquid transfer.

OTHER PRECAUTIONS:

Keep out of reach of children.

SPECIFIC USE(S):

NA

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

PROTECTIVE EQUIPMENT:

EXPOSURE CONTROLS:

Use in a well ventilated area.

RESPIRATORY PROTECTION:

Use NIOSH approved respirator for oil mist to prevent overexposure.

PROTECTIVE GLOVES:

Chemical resistant gloves.

EYE PROTECTION:

Goggles.

OTHER PERSONAL PROTECTION
EQUIPMENT:

Discard contaminated shoes. Chemical resistant materials are required to prevent prolonged or repeated skin contact.

VENTILATION:

General mechanical and/or local exhaust as needed to meet exposure limits if mist in air.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR:

Clear amber liquid. Characteristic odor.

BOILING POINT (F):

> 500 F

(C) NA

VAPOR PRESSURE:

NE

VAPOR DENSITY (AIR=1):

> 1

SOLUBILITY IN WATER:

NA

INTEC MULTI-SOL #3366, New and Improved

9. PHYSICAL AND CHEMICAL PROPERTIES

SPECIFIC GRAVITY: 0.9127
VOC Content (%): NA
VOV Content (%): NE
EVAPORATION RATE: NA
PH: 9.7 (typical @ 10% conc. in H2O)

10. STABILITY AND REACTIVITY

STABILITY DATA: STABLE
POLYMERIZATION: Will Not Occur.
HAZARDOUS DECOMPOSITION: Combustion produces: Oxides of Carbon. Oxides of Sulfur. Hydrogen sulfide. When heated to high temperatures, the following may be produced: Oxides of Metal Reactive volatile hydrocarbons.
INCOMPATIBILITY (MATERIALS TO AVOID): Avoid contact with: Peroxides. Chlorine. Strong acids and oxidizers.
CONDITIONS/HAZARDS TO AVOID: Extreme heat, direct sunlight. Avoid any source of ignition.

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY: NE
EFFECTS OF CHRONIC EXPOSURE: NE
OTHER TOXIC EFFECTS: NE

12. ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: No data at this time
CHEMICAL FATE INFORMATION: No data at this time.
MOBILITY: NA
PERSISTENCE/DEGRADABILITY: NA
BIOACCUMULATIVE POTENTIAL: NA
OTHER ADVERSE EFFECTS: NA

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHODS: Dispose in accordance with Federal, State and Local regulations.

14. TRANSPORT INFORMATION

Please refer to the Bill of Lading/Receiving documents for up to date shipping information.

15. REGULATORY INFORMATION

PRODUCT COMPOSITION CAS#	%	TSCA:	EINECS:	Canada DSL:	CA PROP 65:
Naphthenic oil 64742-53-6	75 - 80	Listed	Listed	Listed	Not Listed

PRODUCT COMPOSITION CAS#	%	CERCLA:	SARA 302:	SARA 313:
Naphthenic oil 64742-53-6	75 - 80	Not Listed	Not Listed	Not Listed

The following components of this material are included in the Massachusetts Substance List and are present at or above reportable levels.

INTEC MULTI-SOL #3366, New and Improved

PRODUCT COMPOSITION CAS#	%	MARTK:
Naphthenic oil 64742-53-6	75 - 80	Listed

The following components of this material are included in the New Jersey Substance List and are present at or above reportable levels.
The following components of this material are included in the Pennsylvania Substance List and are present at or above reportable levels.

16. OTHER INFORMATION

This information was compiled from current, reliable sources and is believed to be correct. As data, and/or regulations change, and conditions of use and handling are beyond our control, no warranty, express or implied, is made as to completeness or continuing accuracy of this information.

***** END OF MSDS *****